



### IS-300/60 (P)

pickle injector

Art.no. red meat 011456

Art.no. poultry 011458

meat: red meat, poultry  
 capacity: up to 2.800 kg/h\* and 1.000 pc/h\*  
 (details are based on minimum injection quantity and maximum forward)  
 injection amount: up to 50 %\*  
 needles: 15 pc 2fold needles 4 mm or 3 mm

#### product description

pickle injector "IS-300/60"  
 with crank drive (needle return point freely selectable)  
 New Twist System  
 with synthetic conveyor belt

#### technical data

control	manual
poultry set for poultry version	stripper stop and guiding rails to assure a controlled product transport
working width	300 mm
clearance	220 mm
number of strokes per minute	1 speed
speed of conveyor mm per stroke	30 or 60 mm per stroke
pump	rotary pump
power	2,2 kW
pressure	approx. 1-2,5 bar
needle system	red meat with 15 pc 2fold needles 4 mm ø 25B poultry with 15 pc 2fold needles 3 mm ø 25B (optional 4fold needles)
voltage	3 x 400 V / 50 Hz (other voltage on request)
total power requirements	approx. 4,3 kW
dimensions	machine length: 1.700 mm width: 925 mm height: 1.950 mm
machine weight	300 kg