

XTRAVAC

Providing Quality with Economical Solutions

XtraVac • TS690A Automatic Tray Sealer

Max. Tray Dimension
 1-up - 590 x 270 mm
 2-up - 277 x 270 mm
 3-up - 172 x 270 mm
 4-up - 120 x 270 mm



Machine Information XtraVac TS690A

Min. Tray Dimension rectangular/round	70 x 70 mm
Tray Height	20 min / 100 max
Max Roll Diameter	340 mm
Max Film Width	690 mm
Film Core	75 mm
Vacuum pump size	202 m3/h - 7.5 hp
Water Cooling	No
Printed Film	Yes
Automatic Die movement	Yes
Cycles per minute	up to 8 seal / 5 gas
Gas pressure/Compressed Air	6 bar
Air consumption per cycle	44L NI/AZ
Electrical connection	220 V 3 ph/60hz, 400 V 3 ph/50hz
Amperage	3.8 KW / 20 A
Machine weight	1203 kg / 1719 lbs
Machine Dimension	131.4 x 43.7 x 61 in 3340 x 1100 x 1550 mm
Shipping weight	1203 kg / 2652 lbs
Shipping Dimension	127.7 x 50 x 72.4 in 3245 x 1270 x 1840 mm

USA
 # 3 SEL Plastic tray dim. 172 mm x 222 mm 3 up
 # 10 SEL Plastic tray dim. 172 mm x 273 mm 2 up

Europe
 230x145mm (XPS tray) SEL 2 up
 265x160mm (1/4 Gastronorm) SEL 2 up
 SEL (Short Edge Leading) - LEL (Long Edge Leading)

Pick Up The Pace!
 The XtraVac TS690A Automatic Tray Sealer will amplify your business with:

- Fully automatic push-bar sealing
- Automatic trim wind up
- Integrated discharge conveyor
- More attractive packages
- Easily changeable tooling
- Optional channelizer for maximum output
- Complete stainless steel construction for durability
- 2 standard operation modes (Seal, Seal & Gas)
- Optional Easy-Peel, and Skin Packaging
- 12-month warranty
- Spare Parts kit included

XTRAVAC

Providing Quality with Economical Solutions

A Division of the Inauen Group · Kansas City, MO
 Tel. 800-728-2999 · Sales@XtraVac.com