

handtmann

***Vacuum filler
VF 200
Decision
for progress***



VF 200

Filling capacity (infinitely variable).

VF 200	5,000 kg/h
VF 200 P	3,600 kg/h

Filling pressure

VF 200	up to 35 bar
VF 200 P	up to 55 bar

Portioning speed

up to 380 portions/min.

Performance table for portioning and linking speeds (tolerance - 10%)

25 g	380 portions/min.
50 g	380 portions/min.
100 g	300 portions/min.
200 g	200 portions/min.

Portioning range

5- 10,000 grammes

with MC control 5-100,000 grammes

Hopper capacity

240 liters

in lower part of hopper 90 liters

Linking gearbox type 34-4

Product return suction

Compensation for 1st portion weight

Electrical

impulse control for clipping machines

standard

(according to specification)

Electric rating

7 kW

Standard accessories

4 linking nozzles 12, 15, 19 and 22 mm dia.

5 filling tubes 12, 16, 22, 30 and 40 mm dia.

Rotor extractor

Operating instructions

Weights and dimensions

VF 200 weight net	1,353 kg
weight gross	1,632 kg

Case dimensions

VF 200 1460x1900x2250 mm

Optional accessories

Automatic holding device

HV 60-6 and HV 60-7

Special linking nozzles with

holding star and brake ring

9, 10, 11, 12, 14, 15, 17,

19, 22, 25 and 28 mm dia.

Clipper attachment set

Double outlet

Type 67-1 manual

Type 67-2 pneumatic

Type 67-4 for

portioning

Technical data

